



**ELECTRICAL FEATURES**

VOLTAGE: 230V 50-60Hz  
 POWER: 1000W +5% -10%  
 POWER DENSITY: 0,92W/cm<sup>2</sup>  
 RESISTANCE: 52,9 OHM (50,4÷58,8)  
 DIELECTRIC STRENGTH: 1500Vx1s  
 INSULATION (500VCC): >50MOHM

**PHYSICAL FEATURES**

THICKNESS: 0,9MM (±0,1)  
 MAX TEMPERATURE: 175°C  
 MIN TEMPERATURE: -40°C

**STANDARD**

QUALITY CONFORMITY: CE (2014/35/UE)  
 ROHS ACCORDANT  
 DIMENSIONAL TOLERANCE: EN ISO 22768 - C  
 STANDARD OF REFERENCE: EN 60335-1 - EN50106

|  |   |  |       |                              |
|--|---|--|-------|------------------------------|
|  |   |  |       |                              |
|  |   |  |       |                              |
|  |   |  |       |                              |
|  |   |  |       |                              |
|  |   |  |       |                              |
| A  | NUOVO TELAIO DEDICATO CON ZONA FREDDA SOTTO TASCA | AG   | GM    | 04/11/19                     |
| REV.   | DESCRIZIONE - DESCRIPTION                         | DRAW   | CHECK | DATE                         |
| DESCRIZIONE - DESCRIPTION<br><b>FLEXIBLE SILICONE HEATER</b> |   | CLIENTE - CUSTOMER<br><b>STEFINOX KFT</b>              |       | SCALA<br>SCALE<br><b>1:1</b> |
| DISEGNATORE - DRAWER<br><b>GM</b>                            |   | CODICE ARTICOLO HEATFOR - HEATFOR ITEM                 |       |                              |
| APPROVAZIONE - APPROVAL<br><b>FC</b>                         |   | CODICE ARTICOLO CLIENTE - CUSTOMER ITEM<br><b>S901</b> |       |                              |
| D  |   |  |       |                              |